

OPALUME



	Sphere Ø400	Sphere Ø500	Cone Ø400	Cone Ø500	Sphere Ø400 Alu	Sphere Ø400	Sphere Ø500	Cone Ø400	Cone Ø500	Sphere Ø400 Alu	Half ellipse Ø400
Lumen output (lm) 730	1000-8500	7000-19000	1000-8500	7000-19000	1000-8500	1000-8500	7000-19000	1000-8500	7000-19000	1000-8500	1000-8500
Lumen output (lm) 740	1000-9500	7000-20000	1000-9500	7000-20000	1000-9500	1000-9500	7000-20000	1000-9500	7000-20000	1000-9500	1000-9500
Lumen output (lm) 830	1700-7500	4400-15800	1700-7500	4400-15800	1700-7500	1700-7500	4400-15800	1700-7500	4400-15800	1700-7500	1700-7500
Lumen output (lm) 840	1800-8000	4700-17000	1800-8000	4700-17000	1800-8000	1800-8000	4700-17000	1800-8000	4700-17000	1800-8000	1800-8000
Lm/W	<146	<146	<146	<146	<146	<146	<146	<146	<146	<146	<146
Tilt	+25°	+25°	+25°	+25°	+25°						
Rotation	+130°	+130°	+130°	+130°	+130°						
IP rating	66	66	66	66	66	66	66	66	66	66	66
IK rating	8	8	8	8	8	8	8	8	8	8	8
Protection class	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
AGC lenses	●	●	●	●	●	●	●	●	●	●	●
Luminous intensity class (max)	G6	G6	G6	G6	G6	G6	G6	G6	G6	G6	G6
Useful time	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h
RGBW (upon request)	●	●	●	●		●	●	●	●		●
Material shade	PMMA	PMMA	PMMA	PMMA	Aluminium	PMMA	PMMA	PMMA	PMMA	Aluminium	PMMA
Color shade	Opaque/transparent	Opaque/transparent	Opaque/transparent	Opaque/transparent	RAL9006 G70	Opaque/transparent	Opaque/transparent	Opaque/transparent	Opaque/transparent	RAL9006 G70	Opal/transparent
Color body	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70
Optional RAL	●	●	●	●	●	●	●	●	●	●	●
Weight	9 kg	13 kg	9 kg	13 kg	9 kg	9 kg	13 kg	9 kg	13 kg	9 kg	9 kg
On/Off	●	●	●	●	●	●	●	●	●	●	●
DALI	●	●	●	●	●	●	●	●	●	●	●
e-Sense Motion	●	●	●	●	●	●	●	●	●	●	●
CLO	●	●	●	●	●	●	●	●	●	●	●
Wire diameter	6-12 mm	6-12 mm	6-12 mm	6-12 mm	6-12 mm						
Pole diameter						48/60 mm	48/60 mm	48/60 mm	48/60 mm	48/60 mm	48/60 mm
Perpendicular arm 180°						●	●	●	●	●	●
Arch arm 180°						●	●	●	●	●	●
Installation cable						●	●	●	●	●	●

Opalume also available for poles with ¾ and ½ inch attachment.