

OPALUME



	Sfärisk Ø400	Sfärisk Ø500	Konisk Ø400	Konisk Ø500	Sfärisk Ø400 alu	Sfärisk Ø400	Sfärisk Ø500	Konisk Ø400	Konisk Ø500	Sfärisk Ø400 alu	Halv elips Ø400
Lumen (lm) 730	2600-9000	5800-19000	1000-8500	7000-19000	1000-8500	1000-8500	7000-19000	1000-8500	7000-19000	1000-8500	1000-8500
Lumen (lm) 740	1000-9500	7000-20000	1000-9500	7000-20000	1000-9500	1000-9500	7000-20000	1000-9500	7000-20000	1000-9500	1000-9500
Lumen (lm) 830	1700-7500	4400-15800	1700-7500	4400-15800	1700-7500	1700-7500	4400-15800	1700-7500	4400-15800	1700-7500	1700-7500
Lumen (lm) 840	1800-8000	4700-17000	1800-8000	4700-17000	1800-8000	1800-8000	4700-17000	1800-8000	4700-17000	1800-8000	1800-8000
lm/W	<146	<146	<146	<146	<146	<146	<146	<146	<146	<146	<146
Tilt	+25°	+25°	+25°	+25°	+25°						
Rotation	+130°	+130°	+130°	+130°	+130°						
IP klass	66	66	66	66	66	66	66	66	66	66	66
IK klass	8	8	8	8	8	8	8	8	8	8	8
Skyddsklass	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
AGC linser	●	●	●	●	●	●	●	●	●	●	●
Avskärmningsklass (max)	G6	G6	G6	G6	G6	G6	G6	G6	G6	G6	G6
Ljusnedgång	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h	L100 B10 100.000h
RGBW (på förfrågan)	●	●	●	●		●	●	●	●		●
Material kupa	PMMA	PMMA	PMMA	PMMA	Aluminium	PMMA	PMMA	PMMA	PMMA	Aluminium	PMMA
Färg kupa	Opal/transparent	Opal/transparent	Opal/transparent	Opal/transparent	RAL9006 G70	Opal/transparent	Opal/transparent	Opal/transparent	Opal/transparent	RAL9006 G70	Opal/transparent
Färg gjutning	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70	RAL9006 G70
Valfri RAL	●	●	●	●	●	●	●	●	●	●	●
Vikt	9 kg	13 kg	9 kg	13 kg	9 kg	9 kg	13 kg	9 kg	13 kg	9 kg	9 kg
On/Off	●	●	●	●	●	●	●	●	●	●	●
DALI	●	●	●	●	●	●	●	●	●	●	●
e-Sense Motion	●	●	●	●	●	●	●	●	●	●	●
CLO	●	●	●	●	●	●	●	●	●	●	●
Vajerdiameter	6-12 mm	6-12 mm	6-12 mm	6-12 mm	6-12 mm						
Stolpdiameter						48/60 mm	48/60 mm	48/60 mm	48/60 mm	48/60 mm	48/60 mm
Rät arm 180°						●	●	●	●	●	●
Böjd arm 180°						●	●	●	●	●	●
Installationskabel						●	●	●	●	●	●

Opalume kan även beställas för stolpar med ¾- och ½-tums infästning.