

## General Data

|  |                                    |  |
|--|------------------------------------|--|
| <b>Product name</b><br>Tibi Ceiling/Wall   | <b>Article. No.</b><br>55260-55267 | <b>Supplement no.</b><br>-402, -495, -496    |
| <b>Contact person, tel., e-mail</b><br>Niclas Thulin, +46 36 2906169<br>niclas.thulin@fagerhult.se |                                    | <b>Declaration established</b><br>2017-08-09 |
|  |                                    | <b>Last updated</b><br>2022-01-27            |

## Supplier Information

|  |  |
|--|--|
| <b>Company information</b><br>Fagerhults Belysning AB<br>SE-566 80 Habo, SWEDEN<br>Org nr 5563218659   | Tel: +46 36-10 85 00<br><a href="http://www.fagerhult.com">www.fagerhult.com</a> |
| <b>Company description</b><br>Fagerhult develops, manufactures and markets professional lighting systems for public environments such as offices, schools, hospitals and industries. |  |
| <b>Certifications</b><br>Fagerhult is certified according to ISO 14001 och ISO 9001  |  |

## Legal requirements regarding the product

|   |
|---|
| <p>If the product contains &gt;0,1 % by weight of substances that are listed on the candidate list within Reach, this is presented in the comments below.</p> <p>The product fulfills Low Voltage-, EMC- and RoHS-directives. Fagerhult is associated with national systems for recycling of electric and electronic waste and the luminaire is recyclable to &gt;90% if it is treated as electrical waste at end of life. Fagerhult is also connected to national packaging recycling systems, therefore we comply with the WEEE and packaging directives.</p> |
|---|

## Structure and content

| Material content             | CAS no. / Reference | % by weight | Comments                           |
|------------------------------|---------------------|-------------|------------------------------------|
| Steel                        | EN 10130            | <30         |                                    |
| Plastic - PMMA               |                     | <27         |                                    |
| Aluminium                    | EN AW 1050-02       | <25         |                                    |
| LED board                    |                     | <8          |                                    |
| Driver                       |                     | <8          | Circuit board is 14% of the driver |
| Powder coating               | polyester/epoxi     | <2          |                                    |
| Plastic - PC                 |                     | <1          |                                    |
| Internal wiring halogen free |                     | <0,5        | CU 50%/FEP 50%                     |
| Rubber                       | EPDM                | <0,3        |                                    |
| Steel zinc plated            | EN 10 142           | <0,3        |                                    |
| Stainless steel              | EN 10088            | <0,2        |                                    |
| Plastic - PA                 |                     | <0,2        |                                    |

## Transports and packing

|  |
|--|
| Transports are mainly done by trucks. Product is packed with corrugated cardboard and/or plastic (PE & EPS). |
|--|

## Environmental impact within the life cycle

|  |
|--|
| The product's main environmental impact during its life cycle is the energy consumed during use. The product's end of life is estimated to 20 years. |
|--|